

July 2021

ULTIMATE STONE ENHANCER H2O TECHNICAL APPLICATION GUIDE

DESCRIPTION

ONE-STEP COLOUR INTENSIFYING IMPREGNATOR

Enhances natural colour & texture *Protects against staining*
Suitable for all types of *from oil & water*
natural stone surfaces *Suitable for internal & external use*

Universeal Ultimate Stone Enhancer is a 100% breathable, premium grade water based stone and masonry enhancing sealer that impregnates to protect against oil and water based stains, whilst enhancing the natural stone colours, leaving a matt finish. **Universeal Ultimate Stone Enhancer** can be used for internal and external application, suitable for the application to all porous textured stone and masonry surfaces. **NOT RECOMMENDED FOR USE ON HIGHLY POLISHED, CERAMIC/GLAZED OR NON-POROUS SURFACES.**

DIRECTIONS FOR USE

Important: Universeal Ultimate Stone Enhancer is very difficult to remove once hardened. Therefore, please read instructions carefully.

- 1) Before application the surface must be completely clean, free from debris and dry.
- 2) **Shake bottle well before use.** Apply an even coat with a low pressure sprayer, paint pad, natural fibre brush or sponge (we do not recommend using a roller), any excess sealer must be completely removed from the surface after 20-30 minutes.
- 3) Apply a second application approximately 45-60 minutes repeating the process. After application it is important that the stone surface is kept completely dry through the curing process, up to 72 hours. Any moisture or water left on the surface within this time may result in the sealer drying inconsistent showing hard to remove white patches.

Please Note: Areas not to be sealed must be protected with masking materials. It is strongly recommended when using coloured grouts that a stain test is completed before proceeding. Results may vary when applying Ultimate Colour Enhancer, depending on the colour, texture and condition of your natural stone. As a rule, it does not provide radical transformational effects when applied to lighter stones, and in particular it cannot enhance common light and grey sandstones such as Kandla Grey. The sealer will always deliver more noticeable results on mid to dark tones or colour infused stones, so if you are unsure, we would recommend you test first to see how the finish works on your particular surface. Beware of application upon floors with under floor heating as the product may dry prematurely. For further enhancement and to provide a shine finish, Universeal Gloss & Seal can be applied.

MAINTENANCE

Clean treated areas with **Universeal Easy Clean**, do not use harsh or abrasive cleaning agents as this can have a negative effect on the treated surface.

COVERAGE

Up to 25m² per litre per coat

This will depend on the porosity of surface. Check the surface after application to ensure full effectiveness of impregnator.

Usage Guidelines

Drying Time	Applications/Coats	Application Method	Dilution
45-60 mins	1-2 coats	Brush/Sprayer/ Paint Pad/ Sponge	Undiluted

PRECAUTIONS

KEEP OUT OF THE REACH OF CHILDREN & PETS

H302: Harmful if swallowed.
H315: Causes skin irritation.
H319: Causes serious eye irritation.
P102: Keep out of reach of children.
P262: Do not get in eyes, on skin, or on clothing.
P280: Wear protective gloves.
P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P302+350: IF ON SKIN: Gently wash with plenty of soap and water.
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P309+311: IF exposed or if you feel unwell: Call a POISON CENTRE or doctor.
P332+313: If skin irritation occurs: Get medical advice.
P337+313: If eye irritation persists: Get medical advice.



Product SDS sheet available to download from the Universeal website.

This information is offered without guarantee. It is the user's responsibility to ascertain the suitability and safety of this product thus assuming all liability and risk thereof. In case of doubt, the product should be tried out in an inconspicuous area. In the event of failure, the manufacturer shall be obliged to replace such product proven defective.

STORAGE INFORMATION

Product shelf life is 12 months from production date (shown on cap) when unopened and stored at room temperature. After opening, use within 3 months. Always shake bottle well before use.

